

EKO MEGATRON SUPER 15W-40

Lubricant for passenger vehicle engines

Description

EKO MEGATRON SUPER 15W-40 is a lubricant of high quality, suitable for gasoline and diesel engines of passenger vehicles and light trucks.

EKO MEGATRON SUPER 15W-40 is mainly recommended for normal change intervals for old generation vehicles with several kilometres of operation.

Applications

- It is suitable for gasoline engines and for diesel engines without diesel particulate filters (DPF), where the manufacturer recommends ACEA A3/B3, API SL, API CF or earlier specifications, and SAE 15W-40 viscosity grade.
- It is suitable for MERCEDES-BENZ engines for which an MB 229.1 lubricant is recommended.
- It is suitable for LPG and CNG engines.

Advantages

- Protection and cleanliness of the engine under normal driving conditions.
- Excellent fluidity of the lubricant during engine start, leading to satisfactory lubrication and sufficient protection of all mechanical parts.
- Oxidation and thermal degradation resistant leading to reduction of deposits and increase of both the lubricant's as well as of the engine's service life.

Specifications

ACEA A3/B3, API SL/CF, MB 229.1.

Typical Characteristics

Properties	Methods	Units	EKO MEGATRON SUPER 15W-40
Κατάταξη κατά SAE	-	-	15W-40
Πυκνότητα, 15°C	ASTM D4052	g/ml	0.882
Κινηματικό Ιξώδες, 100°C	ASTM D445	cSt	13.88
Κινηματικό Ιξώδες, 40°C	ASTM D445	cSt	103.0
Δείκτης Ιξώδους (VI)	ASTM D2270	-	135
Ιξώδες CCS, -20°C	ASTM D5293	cP	6500
Αλκαλικότητα, TBN	ASTM D2896	mg KOH/g	8.2
Θειική Τέφρα	ASTM D874	% w/w	1.1
Σημείο Ροής	ASTM D5950	°C	-30
Σημείο Ανάφλεξης, COC	ASTM D92	°C	228

Health and safety

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze and water, to allow for proper handling.

30 January 2025

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511.

Advice on safe handling is provided in the Safety Data Sheet.