



EKO FORZA PLATINUM FORMULA LE 10W-40

Lubricant for commercial vehicle engines

Description

EKO FORZA PLATINUM FORMULA LE 10W-40 is a fully synthetic engine lubricant with a low level of SAPS (low-SAPS), designed for on and off-road diesel engines equipped with modern emission control systems EGR, SCR and diesel particulate filters (DPF).

It is suitable for on-road EURO I to EURO VI engines and for off-road EU Stage V and older engines.

Applications

- Suitable for modern heavy-duty diesel engines that operate on and off highways and require low SAPS engine oils.
- Suitable for compressed natural gas (CNG) engines.
- Meets all modern engine manufacturer requirements, allowing for the use of one lubricant for all commercial and earthmoving vehicles in mixed vehicle fleets of different manufacturers.
- Compatible with older technology engines.

Specifications

ACEA E6, E7, E8, E9, E11, API CI-4, CATERPILLAR ECF-1a, CUMMINS CES 20076/20077, DEUTZ DQC IV-18 LA/DQC TTCD, JASO DH-2, MTU Type 3.1, RENAULT RXD/RGD. Meets the requirements of MAN M3477, MAN M3271-1.

Approvals

DTRF 15C110 (228.51), VOLVO VDS-3, RENAULT VI RLD-2, MACK EO-N.

Suitable for use

VOLVO CNG

Advantages

- Effective emission control.
- Increased engine cleanliness and excellent wear protection, resulting in longer drain intervals.
- Excellent performance at low temperatures.
- Low SAPS engine oil: maintains effectiveness and prolongs lifespan of diesel particulate filters (DPF).
- Suitable for mixed vehicle fleets and equipment of different manufacturers and varying age.

Typical Characteristics

Properties	Methods	Units	EKO FORZA PLATINUM FORMULA LE 10W-40
SAE Viscosity Grade	-	-	10W-40
Density, 15°C	ASTM D4052	g/ml	0.862
Kinematic Viscosity, 100°C	ASTM D445	cSt	15.15
Kinematic Viscosity, 40°C	ASTM D445	cSt	101.9
Viscosity Index (VI)	ASTM D2270	-	156
CCS Viscosity, -25°C	ASTM D5293	cP	5800
Base Number, TBN	ASTM D2896	mg KOH/g	10.2
Sulfated Ash	ASTM D874	% w/w	0.92
Pour Point	ASTM D5950	°C	-36
Flash Point, COC	ASTM D92	°C	244

Health and safety

Protect the environment while disposing of used product. Used lubricants should be collected at specific points to ensure they do not pollute the environment. Do not mix with solvents, brake fluids, antifreeze fluids and water, to allow for proper handling.

30 January 2025

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. +30 210 5509 511.

Advice on safe handling is provided in the Safety Data Sheet.