



EKOGREASE EM 3

Lithium grease

Description

EKOGREASE EM 3 is a top quality, lithium-based grease, enhanced with antioxidants and corrosion inhibitors.

Specifications

DIN 51825 K3K-30.

Applications

- Meets all general lubrication needs of vehicles and machinery.
- Suitable for the lubrication of both plain and roller bearings in vehicles and equipment operating off road (construction, farming, mining, quarrying).
- Suitable for a vast array of industrial applications requiring lithium grease without EP additives.
- Ideal for the lubrication of roller bearings in electric motors.

Advantages

- Mechanical stability and resistance to shearing.
- Resistance to washout by water.
- Enhanced adhesion to metal surfaces.
- Excellent pumpability even at low temperatures.
- Optimal protection against corrosion.
- Effective performance over a wide temperature range (-30°C to +130°C).

Typical Characteristics

Properties	Methods	Units	EKOGREASE EM 3
Soap Base	-	-	Lithium
Base Oil	-	-	Mineral Oil
Colour	Visual Inspection	-	Amber
NLGI	ASTM D217	-	3
Dropping Point	ASTM D2265	°C	190
Base Oil Viscosity at 40°C	ASTM D445	cSt	110
Worked Penetration, 60 strokes	ASTM D217	mm ⁻¹	220-250
Operating Temperature	-	°C	-30°C to +130°C

Health and safety

Protect the environment while disposing of used product.

30 January 2025

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. + 30 210 5509511.

Advice on safe handling is provided in the Safety Data Sheet.