

EKOGREASE LC 2

Calcium grease

Description

EKOGREASE LC 2 is a calcium grease providing excellent adhesion to metal surfaces and superior water washout resistance.

Applications

- EKOGREASE LC 2 is suitable for the lubrication of chassis of both automotive units and agricultural equipment operating at low or moderate load capacity and temperatures of up to 80°C, as well as under conditions potentially involving contact with water.
- This grease can be used for a wide range of general lubrication applications.

Advantages

- Increased resistance to washout by water.
- Effective protection against rust and corrosion.
- Excellent adhesion to metal surfaces.
- Good pumpability at low temperatures.
- Shear resistance and stability.

Specifications

DIN 51825 K2E-30.

Typical Characteristics

Properties	Methods	Units	EKOGREASE LC 2
Soap Base	-	-	Calcium
Base Oil	-	-	Mineral Oil
NLGI	ASTM D217	-	2
Base Oil Viscosity at 40°C	ASTM D445	cSt	100
Colour	Visual Inspection	-	Blond
Dropping Point	ASTM D566	°C	90
Worked Penetration, 60 strokes	ASTM D217	mm ⁻¹	265-295
Oil Separation	ASTM D1742	-	max 5
Flash Point	ASTM D92	°C	250
Copper Corrosion	ASTM D4048	-	1b
Rust Protection	ASTM D1743	-	Pass
Operating Temperature	-	°C	-30°C to +80°C

Health and safety

Protect the environment while disposing of used product.

30 January 2025

This data sheet provides basic information on the product as at the date of drafting. For further information regarding applications, please contact EKO ABEE Technical Support, tel. + 30 210 5509511.

Advice on safe handling is provided in the Safety Data Sheet.